# EZ-COLOR CUT LETTERING SIGN VINYL



Premium calendered sign vinyl available in a wide variety of colors that cuts and weeds easily and is ideal for banner graphics, decals, and cut lettering applications.

#### EZ-Color™

Excellent dimensional stability

Cuts and weeds easily

Available in a variety of colors/patterns and standard roll sizes

For ease of installation, apply cut letters with RTape® Conform® 4075RLA

Soft in nature, adaptable for conforming to curves or flat surfaces

3 mil gloss vinyl facestock rated for <6 years of outdoor durability

Moderate peel, moderate tack permanent adhesive

78# paper liner

Specifically formulated for banner graphics and lettering

Print Compatibility: Thermal

#### **Applications**

**Banner Graphics** 

**Cut Lettering** 

Decals

Holiday Décor

Point-of-Purchase

Signage

**Bumper Stickers** 

Fleet Markings

Safety Signage

Commercial Signage

**Identification Markings** 

Appliance Labels

Nameplates





## **EZ-COLOR** CUT LETTERING SIGN VINYL







### **STOCKED PRODUCTS** ▶

SKU#	Size
CVCL2450A	24" x 50 yd
CVCL4850A	48" x 50 yd
CVWH2450A	24" x 50 yd
CVWH4850A	48" x 50 yd
CVSTW2450A	24" x 50 yd
CVSTW4850A	48" x 50 yd
CVBR2450A	24" x 50 yd
CVBR4850A	48" x 50 yd
CVBY2450A	24" x 50 yd
CVBY4850A	48" x 50 yd
CVSF2450A	24" x 50 yd
CVSF4850A	48" x 50 yd
CVGO2450A	24" x 50 yd
CVGO4850A	48" x 50 yd
CVOR2450A	24" x 50 yd
CVOR4850A	48" x 50 yd
CVSP2450A	24" x 50 yd
CVSP4850A	48" x 50 yd
CVTR2450A	24" x 50 yd
CVTR4850A	48" x 50 yd
CVBT2450A	24" x 50 yd
CVBT4850A	48" x 50 yd
CVCD2450A	24" x 50 yd
CVCD4850A	48" x 50 yd
CVBG2450A	24" x 50 yd
CVBG4850A	48" x 50 yd
CVPU2450A	24" x 50 yd
CVPU4850A	48" x 50 yd
CVOB2450A	24" x 50 yd
CVOB4850A	48" x 50 yd
CVMB2450A	24" x 50 yd
CVMB4850A	48" x 50 yd
	24" x 50 yd
CVBTB4850A	48" x 50 yd
CVBU2450A	24" x 50 yd
CVBU4850A	48" x 50 yd
CVSB2450A	24" x 50 yd
CVSB4850A	48" x 50 yd
CVDB2450A	24" x 50 yd
CVDB4850A	48" x 50 yd
	CVCL4850A CVWH2450A CVWH2450A CVWH4850A CVSTW2450A CVSTW2450A CVBR2450A CVBR2450A CVBR2450A CVBY2450A CVSF2450A CVSF2450A CVGO2450A CVGO2450A CVGO2450A CVGVBR50A CVSP2450A CVSP2450A CVSP2450A CVSP2450A CVSP2450A CVSP2450A CVFR2450A CVFR2450A CVFR2450A CVFR2450A CVFR2450A CVFR2450A CVBR2450A

Code/Color	SKU#	Size
EZ-Color™ Cut Vinyl		
100 AI- C	CVAG2450A	24" x 50 yd
<b>196</b> Apple Green	CVAG4850A	48" x 50 yd
20 Kalla Caran	CVKG2450A	24" x 50 yd
38 Kelly Green	CVKG4850A	48" x 50 yd
28 Medium Green	CVGR2450A	24" x 50 yd
28 Medium Green	CVGR4850A	48" x 50 yd
18 Hunter Green	CVHG2450A	24" x 50 yd
16 Hullter Green	CVHG4850A	48" x 50 yd
<b>90</b> Silver	CVSI2450A	24" x 50 yd
90 Silvei	CVSI4850A	48" x 50 yd
31 Medium Gray	CVGY2450A	24" x 50 yd
31 Medium Gray	CVGY4850A	48" x 50 yd
<b>73</b> Dark Gray	CVDG2450A	24" x 50 yd
	CVDG4850A	48" x 50 yd
<b>12</b> Black	CVBK2450A	24" x 50 yd
	CVBK4850A	48" x 50 yd
22 Matte Black	CVSTB2450A	24" x 50 yd
ZZ Marte Black	CVSTB4850A	48" x 50 yd

# **EZ-COLOR** CUT LETTERING SIGN VINYL

■ Indoor & Outdoor Series: Roll Size (in)



<sup>\*</sup>Other sizes may be available upon request.



### **TECHNICAL DATA** ▶

		CV300
Physical Properties		
Finish		Gloss
Color		Various - See Chart
Adhesive		Permanent - P22
Film		Premium Calendered Vinyl
Liner		78#
Opacity		92% minimum
Gloss Level		CD > 70%
Thickness	Film	$3.0 \pm 0.2  \text{mil}$
	Film + Adhesive	4.0 ± 0.2 mil
	Total Thickness	8.5 ± 0.2 mil
Adhesion*	SS 15 min room temp dwell	50 oz/in minimum
	SS 24-hr room temp dwell	70 oz /in minimum
Weight	Film + Adhesive	110-125 gsm
	Total w/ Liner	230-250 gsm
Printability		Thermal

		CV300
Conditions for Use		
	Shelf Life*	1 year
	Outdoor Durability**	Up to 6 years
	Min Application Temp	40 °F (4 °C)
	Service Temp Range	-50° to 150°F (-46° to 66°C)
	Solvent Resistance***	Good
	Water Resistance	Excellent

Store open rolls horizontally, suspended through the core with suitable bar. Do not store vertically on end; this will cause cracking of the sheeting light source.

\*When stored at 75° F and 50% relative humidity

\*\*Mid-continental U.S. vertical

\*\*\*Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

